

Fig. 1




Fig. 2






Fig. 3

Scenario 1: printing and authentication of an original analog form



Scenario 2: printing and authentication of a non-original analog form








Fig. 5




<u>601</u>

Fig. 6



<u>701</u>

Fig. 7



Watermarked digital representation 813

FIG. 8








Fig. 9



1001

Fig. 10








Fig. 11





Fig. 12




1301

Fig. 13

403										<i>l</i>	/	1405	i) 											
ð	Mer 10 W Prov	diàSe /syboss idence	c Tec et Sires RI 0290	hhol t, sutt	oğle 601	s ĽL	: ·	**************************************	# 1.2. # 1.2.	7.	<del></del>	Date	0	4/1:	5/Q3			10	04				•	
	Pay to coder	of	B hous			3m o hu		d thi	irty fo	our a	ind 4	14/10	0	1.		<b>.</b> \$ [	2	,23	4.44			•		
	— ⊕sa	mple	Bank	•	. •	•	•		•	•			•	•	÷ .	* :	•	12	-10	. · •	•	•	•	
•	•		•	•		: •	•	•	•	•	•			•	•	•.	÷	•.	•	•		-	•	
	. •	•	•		•	•			•	۵,	٠.	•	,	٠,	•	S a	m	p16	э (	3 a	m	plŧ	•	F
For																								

Fig. 14



1501

Fig. 15

Obviously, the multiple CDP digital image has to be printed on the printer that will be used in the application, with the same printing parameters, and has to be scanned with the scanner of the application, with the same parameters as well. Not observing this, or using the wrong threshold and parameters, may, may lead to a less reliable detection, if not to completely wrong results.

1601

1602




Fig. 16


243	228	210	236
59	195	114	189
155	117	158	45
124	5	203	104

12	27	45	19
196	60	141	66
100	138	97	210
131	250	52	151


1702

44	36	24	10
198	20	167	83
97	159	135	198
106	299	10	172

Fig. 17



vap0 1801



vapk 1803



VM 1805




Fig. 18